

GEORGIA INSTITUTE OF TECHNOLOGY OFFICE OF SPONSORED PROGRAMS
Office of Research Administration, Compliance, Training & Technologies (ReACTT)
RESEARCH REPORT APPROVAL SHEET

Project No. C-41-X87
Lab/School/Center: Physics

1. GENERAL

A. Report Title Final Report
B. Author(s) and/or PD/PI Andrew Zangwill Phone 404-894-5202
C. Period Covered: 8/1/97-10/31/03 Due Date

2. REPORT

A. Deliverable Line Number (from Deliverable Schedule) 3
B. Type of Report:
☐ Monthly ☐ Contract Mgt. ☐ Progress ☐ Semi-Annual ☐ Cost & Performance
☐ Annual ☐ Quarterly ☒ Final Report ☐ Other
C. Draft Copy for Sponsor Approval ☐
D. Approval Copy for Distribution ☐ Send Copy to Sponsor ☐ Send Master to Sponsor ☐ Return Master to PD/PI

3. SECURITY CLASSIFICATION

☒ Unclassified ☐ Publication Delayed Until (Specified industry contracts only)
☐ Confidential ☐ Secret ☐ Top Secret *Note: Classified reports are not to be emailed under any circumstances.*
☐ Other (i.e. ITAR, export controlled, etc.)

4. DATA RESTRICTIONS ☐ Yes ☒ No

Proprietary Data (Confidential Disclosure); Export License; Trade Secret; Copyright or Publishing Restrictions; Patentable Technology *Note: Reports containing Proprietary Data, Export Controlled data, Trade Secret, Copyright or Patentable Technology should be filed as a restricted report in the restricted section of the Georgia Tech Library. Patentable technology or any technology of commercial value (e.g., software) should be filed with the Office of Technology Licensing. In the event open access to the report is desired, you must edit the report to remove any and all restricted data.*

5. PRINTING and DISTRIBUTION INSTRUCTIONS TO OSP/ReACTT

(Unless otherwise indicated, printing charges will be assessed against project number. If the project has been terminated, charge number to use:)

A. Number of copies to be printed:
☐ Sponsor ☐ School / Lab ☐ Other ☐ Total
B. Printing Desired ☐ One-Sided ☐ Two-Sided
C. Binding Desired: ☐ Staple ☐ Staple & Tape ☐ Spiral Bind
☐ Velobind ☐ Other
D. Cover Desired: ☐ Standard White ☐ Other Color (Specify) ☐ None
E. Approval of Check Copy by School/Lab before binding: ☒ No ☐ Yes (If yes, phone:)

OSP/ReACTT will retain one copy of each report throughout the life of the project. When the project is closed, OSP/ReACTT will make an additional copy of all reports and forward both sets to the campus library archives.

6. DISTRIBUTION BY:

☒ Lab/School/Center *Paper copies: If distribution by lab/school**, attach transmittal letter. Date mailed: (This is the date that OSP/ReACTT will enter into the database).
NOTE: Due to storage constraints, only one copy is to be provided to OSP / ReACTT. When the project is closed, ReACTT will make the required second copy for the library archives and circulation*

Emailed to DOE 8/22/04

Emailed reports: Send email copy** to ocareports@oca.gatech.edu.

**Final reports require the approval of the Lab/School/Department/Center head. A Research Report Approval Sheet bearing that person's signature must be forwarded to ReACTT before the final report shipment date will be entered into the database:

ReACTT
Office of Sponsored Programs
Centennial Research Building, Room 117A
Mail Code 0420 Campus

☐ OSP/ReACTT If distribution by OSP/ReACTT, the signature of the ReACTT employee handling the report and the mailing date are to be entered here:
Distributed by:
Date mailed:

☐ Research Security If distribution by Research Security, the signature of the Research Security employee handling the report and the mailing date are to be entered here:
Distributed by:
Date mailed:

7. SIGNATURES and APPROVALS

A. PD/PI Date 8/23/04
B. Division Chief or Branch Head Date
C. Lab/School/Department/Center Head James Taylor Date 8/23/04
(Required for final reports)

2004 FEB 25 PM 3 39
TRC/OSP

8.25.4

FINAL REPORT

Submitted to the
Division of Materials Sciences
Department of Energy
Washington DC 20545

SUBMITTED BY:	Andrew Zangwill Georgia Institute of Technology Atlanta, GA 30332
TITLE:	Kinetics of Heteroepitaxy
CONTRACT #:	DE-FG02-97ER45658
GRANT PERIOD:	9/1/00-8/31/02
TOTAL AMOUNT:	\$130,000

OVERVIEW

Most of the funds for this two-year grant were used to support Dr. Max Petersen, a post-doctoral fellow who joined my group in February 2000. He is now a senior researcher at Accelrys, Inc., a scientific simulation concern. The remainder of the funds provided summer support for the PI. This led to a collaboration with a Georgia Tech colleague, Prof. Michael Schatz, and two physicists at the Weizmann Institute. No Georgia Tech graduate students were supported on this grant. Our activities were reported in:

1. *Ripples Settle Surface Behavior*, A. Zangwill, Physics World, September 2000, pp. 23-24.

2. *Convective Instability of Strained Step-Flow Growth*, N. Israeli, D. Kandel, M. Schatz, and A. Zangwill, Surface Science **494**, L735 (2001).

3. *Level Set Approach to Reversible Epitaxial Growth*, M. Petersen, C. Ratsch, R.E. Caflisch, and A. Zangwill, Physical Review E **64**, 061602 (2001).

4. *Advances in Aggregation*, A. Zangwill, Nature **411**, 651 (2001)

5. *Homoepitaxial Ostwald Ripening*, M. Petersen, A. Zangwill, and C. Ratsch, Surface Science **536**, 55 (2003).

DETAILS

I begin with Papers 3 and 5 above, which represent the core of the research. Our interest was to extend the so-called "level-set" method [1] to simulate **reversible** epitaxial growth. This is the situation where atoms are forbidden to detach from step edges.

To model irreversible growth, the level set method solves the diffusion equation on every terrace (with absorbing boundary conditions) to find the monomer density $c(\mathbf{r})$. For each island step edge, the growth velocity is

$$v_+ = -a^2 D \frac{\nabla c}{\nabla n} \Big|_{\text{step}}$$


where a is the lattice constant and D is the terrace diffusion constant. The key to the method is the algorithm used to track the motion of each terrace. Island nucleation is treated as a stochastic process

Dr. Petersen's task was to generalize the level set (LVST) method to handle reversible growth—the situation where any atom can detach at will from any step edge—in a manner that does not create additional computational overhead. This is an absolute prerequisite to any practical level set approach to heteroepitaxy. He was completely successful, albeit after a very long period of code development and debugging. There are (at least) two ways to take account of detachment. One alters the boundary condition on the diffusion equation [2]. This considerably complicates the level set formalism. As an alternative, we supplemented the growth velocity above with a “detachment velocity”


$$v_- = a^2 D_{\text{det}} p_{\text{esc}} \lambda.$$

Here, D_{det} is the detachment rate from an edge, p_{esc} is the probability that a detaching atom actually escapes from the island, and λ is the linear density of singly coordinated edge atoms. It is also necessary to decide where to put the detached atoms and to invent a stochastic algorithm to deal with very small islands that disintegrate due to detachment. When all this is done, we find that the submonolayer island size distribution computed by LVST agrees quantitatively with the corresponding KMC distribution (see figure at right). From top to bottom, the three panels have $D_{\text{det}}/D = 10^{-4}, 5 \times 10^{-3}, \text{ and } 10^{-3}$.

This was encouraging, but not decisive until we compare the computation time needed for the LVST simulation with the time required to




perform the KMC simulations. This is shown in the figure below.



As suggested above, the CPU time for a KMC simulation increases rapidly as the detachment rate increases. The LVST simulation suffers negligibly in comparison. From our earlier KMC simulations of 3D island formation, we know that a value of $D_{\text{det}}/D=0.01$ is typical for realistic systems and temperatures. The graph above tells us that the corresponding LVST simulation (not optimized) would run at least five times faster.

To further check the correctness of our methodology, we elected to study the problem of Ostwald ripening for 2D epitaxial islands. That is, how does the “as-grown” island size distribution (depicted earlier) change when the system is held at temperature after the deposition flux is turned off? This is a subject of considerable experimental interest [3]. It was also studied not long ago using KMC simulations [4]. Oddly, the latter authors did not compare their simulated island size distributions with the current best analytic theory of ripening in two dimensions [5]. This mean field theory predicts that the distribution approaches an asymptotic (late time) form that depends only on the coverage. The figure below shows that our higher coverage results ($\phi=0.25$) follow the trend of the analytic theory very well. Note that the data from different annealing times (dots) all collapse onto one curve.



Finally, a casual lunch conversation with a Georgia Tech colleague—an experimental fluid dynamics expert—led us to re-analyze a model of strain-induced step-bunching that was introduced a few years ago [6]. The original study began with a uniform array of steps in step-flow motion and asked the usual question: does a periodic perturbation of step separations grow or decay as growth proceeds? We asked a question that is more typical in the field of hydrodynamics: does a localized perturbation spread more rapidly than it propagates (absolute instability) or does it propagate more rapidly than it spreads (convective instability)? The distinction is important because a convectively unstable system is sensitive to subsequent perturbations while an absolutely unstable system is not. This has implications for morphological patterning at the nanoscale.

As reported in Paper 2 above, we discovered that the model we studied is indeed convectively unstable toward step bunching over a very wide range of material parameters and growth conditions. The most interesting consequence of this fact arises if we supplement the uniform growth flux with a highly collimated “pencil” of atoms that can be scanned across the surface to perturb the step pattern locally. One can also imagine using the “shadow” cast by a scanning tunneling microscope to accomplish the same thing (with reverse contrast). When this raster is used to “write” a single pattern on the flowing steps, the convective nature of the growth causes “echoes” of the pattern to appear periodically on the surface. Non-linear effects eventually become important, but our calculations suggest that the echoes reproduce the original pattern many times with surprising good

fidelity. To our knowledge, this is an entirely novel way to generate lateral pattering in an otherwise featureless step-flow situation.

References

1. M. F. Gyure, C. Ratsch, B. Merriman, R.E. Caflisch, S. Osher, J.J. Zinck, and D.D. Vvedensky, Phys. Rev. E **58**, R6927 (1998).
2. G.S. Bales and A. Zangwill, Phys. Rev. B **55**, R1973 (1997).
3. See, e.g, K. Morgenstern, G. Rosenfeld, and G. Comsa, Surf. Sci. **441**, 289 (1999) and references therein.
4. P.-M. Lam, D. Bayayoko, and X.-Y. Hu, Surf. Sci. **429**, 161 (1999).
5. J.H. Yao, K.R. Elder, H. Guo, and M. Grant, Phys. Rev. B **47**, 14110 (1993).
6. J. Tersoff, Y.H. Phang, Z. Zhang, and M.G. Lagally, Phys. Rev. Lett. **75**, 2730 (1995); F. Liu, J. Tersoff, M.G. Lagally, Phys. Rev. Lett. **80**, 1268 (1998).